

2SD1819A


SOT-323 NPN

/ Features


， ， 2SB1218A

/ Applications

/ Equivalent Circuit



/ Pinning




/ Marking

/ Absolute Maximum Ratings(Ta=25 –)

/ Electrical Characteristics(Ta=25 –)

		μ				
		μ				
						μ
						μ


/ Electrical Characteristic Curve



/ Package Dimensions


SOT-323

单位: mm




Dimensions In Millimeters			Dimensions In Millimeters		
Symbol	Min	Max	Symbol	Min	Max
A	1.95	2.35	C	0.30	0.50
L	2.00	2.2	L1	0.85	1.15
E	1.20	1.40	a	0.20	0.40
P	1.15	1.35	P	7°	

/ Marking Instructions



() / Whp shudwxuh Suriloh i ru LU Uhior z Vroghulqj+Se0luhh,



± ± ± ±

/ Resistance to Soldering Heat Test Conditions

± ±

/ Packaging SPEC.

封装形式	包装数量					包装尺寸		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205

/ Notices