

MMBTA06

Rev.FApr.-2017

/ Descriptions

SOT-23 NPN Silicon NPN transistor in a SOT-23 Plastic Package.


• / Features

MMBTA56
Complementary to MMBTA56.


v / Applications

Ideal for medium power amplification and switching.

≡ / Equivalent Circuit



λ / Pinning






PIN1 Base PIN 2 Emitter PIN 3 Collector

⌂ / Marking

h_{FE} Range	100~300
Marking	HK1G


Electrical Characteristic Curve



/ Package Dimensions


SOT-23

单位; mm



Dimensions In Millimeters			Dimensions In Millimeters		
Symbol	Min	Max	Symbol	Min	Max
L	2.2	2.7	C1	1.20	1.20
L1	0.45	0.65	C	0.90	1.20
A	1.15	1.50	K	0.05	0.20
B	2.70	3.10	M	0	0.10
E	1.70	2.10		0.20MIN	
E1	0.85	1.05		7°	
b	0.35	0.55			

/ Marking Instructions



H


K1G

Note:

H: Company Code.

K1G: Product Type Code.

∫ 7 V () / Whp shrdwxrh Prrioh irr IU Uhiow Vroghriqj+Pe-Frhh,



Note:

- | | | | |
|---|----------|-------------|---|
| 1 | 25 ~ 150 | 60 ~ 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

4 Y / Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp:260±5 Time:10±1 sec

— / Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-23	3,000	10	30,000	6	180,000	7" x8	180×120×180	390×385×205

v / Notices