

/ Descriptions

SMAF

Surface Mount Schottky Barrier Rectifier, Reverse Voltage: 20 to 200 V, Forward Current:1.0A ,SMAF thin package.

/ Features

Low power loss, high efficiency, High forward surge current capability, For use in low voltage, high frequency inverters, and polarity protection applications,For surface mounted applications.Halogen free product.

/ Applications

General purpose.

/ Equivalent Circuit




/ Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size



/ Marking

See Marking Instructions.


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating								Unit
		SS12F	SS14F	SS16F	SS18F	SS110F	SS112F	SS115F	SS120F	
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	20	40	60	80	100	120	150	200	V
Maximum RMS voltage	V _{RMS}	14	28	42	56	70	84	105	140	V
Maximum DC Blocking Voltage	V _{DC}	20	40	60	80	100	120	150	200	V
Maximum Average Forward Rectified Current	I _{F (AV)}	1.0								A
Peak Forward Surge Current,8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	40				30				A
Typical Junction Capacitance ¹⁾	C _i	110		80						pF
Typical Thermal Resistance ²⁾	R _{θJA}	95								℃/W
Operating Junction Temperature Range	T _j	-55~+125								℃
Storage Temperature Range	T _{stg}	-55~+150								℃

Note:


- 1) Measured at 1MHz and applied reverse voltage of 4 V D.C.
- 2) P.C.B. mounted with 0.2 X 0.2" (5 X 5 mm) copper pad areas.

/ Electrical Characteristics(Ta=25)


Parameter	Symbol	Test Conditions	数值 Rating								Unit
			SS12F	SS14F	SS16F	SS18F	SS110F	SS112F	SS115F	SS120F	
Max Instantaneous Forward Voltage	V _F	I _F =1.0A	0.55		0.70		0.85		0.90		V
Maximum DC Reverse Current at Rated DC Reverse Voltage	I _R	T _a =25℃	0.3				0.2		0.1		mA
		T _a =100℃	10				5.0		2.0		



/ Electrical Characteristic Curve



/ Package Dimensions




/ Marking Instructions

Marking

Type number	Marking code
SS12F	SS12
SS14F	SS14
SS16F	SS16
SS18F	SS18
SS110F	SS110
SS112F	SS112
SS115F	SS115
SS120F	SS120



/ Marking Instructions



SS12

1 *


3 *

Note:

SS12 Product Type Code

Lot No. Code The 1st * means:YM Code The last 3 * means:little Lot
No Code

() /



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 | 5 | 5 | 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260 5 Time:10 1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SMAF	3000	5	15000	5	75000	7" ×11	185X180X105	390X385X205

/ Notices